

Opal5

5 Port Entry-level Unmanaged DIN-Rail Switches



» Overview

Opal5 unmanaged 5-port switch is specially designed for automation control applications. It is equipped with one fast Ethernet fiber/RJ45 optional port and 4 10/100Base-TX RJ45 ports. Opal5 supports SC/ST/SFP type fiber ports, redundant power inputs, metal housing with IP30 protection class, thus ensuring fast and reliable data transmission in harsh industrial environments. Opal5 provides both standard (-10°C to 60°C) operating temperature range model and wide (-40°C to 75°C) operating temperature range models to meet different applications.

» Key Features

- 1 Fast Ethernet fiber/RJ45 optional port, 4 10/100Base-T(X) ports
- Both standard and wide operating temperature models are available
- IP30 protection class
- UL508, Class I Div 2, ATEX Zone 2, IECEx, CE, FCC

» Product Specifications

> Technical Specification
- Standard

IEEE 802.3i (10Base-T)

IEEE 802.3u (100Base-TX and 100Base-FX)

-Switch Properties

MAC Table: 2K

Packet Buffer: 1Mbit

Packet Forwarding Rate: 0.75Mpps

Switching Delay: <10 μ s

-Interface

Fast Ethernet Port:

100Base-FX, SM/MM, SC/ST connector

100Base-X, SFP slot

10/100Base-T(X), RJ45 port

-LED

LEDs on Front Panel

Power LED: PWR1, PWR2

Interface LED: Link/ACT, Speed (RJ45 port); Link/ACT (Fiber port)

-DIP-Switch

Enable/Disable broadcast storm protection

-Power Requirements

Power Input: 12-48VDC/18-30VAC

Power Terminal:

4-pin 5.08mm-spacing plug-in terminal block

Power Consumption: <3.4w

Overload Protection: Support

Reverse Protection: Support

Redundancy Protection: Support

-Physical Characteristics

Housing: Metal

Cooling: Natural convection, fanless

Protection Class: IP30

Dimension: 30mm \times 115mm \times 68mm (W \times H \times D)

Weight: 0.2Kg

Mounting: DIN-Rail or Panel Mounting

-Environmental Limits

Operating Temperature:

-10°C to +60°C (Opal5-E)

-40°C to +75°C

Storage Temperature: -40°C to +85°C

Ambient Relative Humidity: 5-95% (non-condensing)

-Quality Assurance

MTBF: 6,119,957 hrs

Warranty: 5 years

-Approvals

UL508, Class I Div 2, ATEX Zone 2, IECEx, CE, FCC

-Industry Standard

EMI:

FCC CFR47 Part 15, EN55022/CISPR22, Class A

EMS:

IEC61000-4-2(ESD): ±6kV (contact), ±8kV (air)

IEC61000-4-3(RS): 10V/m (80MHz–2GHz)

IEC61000-4-4(EFT): Power Port: ±2kV; Data Port: ±1kV

IEC61000-4-5(Surge): Power Port: ±1kV/DM, ±2kV/CM; Data Port: ±1kV

IEC61000-4-6(CS): 10V (150kHz–80MHz)


Machinery:

IEC60068-2-6 (Vibration)

IEC60068-2-27 (Shock)

IEC60068-2-32 (Free Fall)

Mechanical Drawing



Ordering Information

Opal5-X-Ports-Connector-PS

X

Operating temperature range

E

-10 to +60°C operating temperature

None

-40 to +75°C operating temperature

Ports

5T

5 10/100Base-T(X) RJ45 ports

1S4T

1x100Base-FX, single mode fiber port; 4x10/100Base-T(X) RJ45 ports

1M4T

1x100Base-FX, multi mode fiber port; 4x10/100Base-T(X) RJ45 ports

1SFP4T

1 100Base-X, SFP slot; 4 10/100Base-T(X) RJ45 ports

Connector

100M fiber port specifications

SC05

SC connector, multi-mode, 1310nm, 5km

ST05

ST connector, multi-mode, 1310nm, 5km

SC40

SC connector, single-mode, 1310nm, 40km

ST40

ST connector, single-mode, 1310nm, 40km

SC60

SC connector, single-mode, 1310nm, 60km

SC80

SC connector, single-mode, 1550nm, 80km

None

No 100M fiber port

PS

LV-LV

12-48VDC/18-30VAC, redundant power inputs

Accessories

100Base-X SFP module

Please refer to the 100Base-X SFP module ordering list

DT-BGAZ-13

Panel for Panel mounting

DT-FCZ-RJ45-01

Dustproof cover for RJ45 port

Version:2018-02-12 09:59:35